



Tow-Trust Towbars

Important: Please read General Notes overleaf before fitting

Issue 1

TD975 DAIHATSU FOURTRACK COMMERCIAL & ESTATE (3500KG, LEAF SPRING) 84 - 93

Item	Qty	Description	Item	Qty	Description
A	1	Crossmember	C	4	12 x 38 Flat Washers
B	1	Extension Bar	D	4	10 x 40 Flat Washers
			E	4	M16 x 50 Bolts, Nuts & S/P Washers
			F	4	M12 x 35 Bolts, Nuts & S/P Washers
			G	8	M10 x 30 x 1.25 Bolts & S/P Washers
			H	2	Bolt Caps

1. Remove the central towing eye. Remove the fog light and rear steps.
2. Using Item G with Item D under each bolt head, loosely bolt Item A to the outer existing threaded holes.
3. Using Item G, loosely bolt the angle brackets on Item A to the existing inner bumper mounting points.
4. Using Item F with Item C under each bolt head, bolt Item A to the four existing towing eye mounting points.
5. Using Item E, bolt Item B to Item A.
6. Using Item E bolt the ball bracket and the wiring plate (not supplied in this kit) to the mounting plate.
7. Fully tighten all nuts and bolts and ensure the towbar is rigid and secure.
8. Replace rear steps and remount the fog light.

Note: nose load limits and vehicle manufacturers trailer / caravan weight limits must be observed.

